

Green Jet, PW, Twock-H, Skid Fuego, IWD

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93



HOT WATER WEED REMOVAL SYSTEM

GREEN JET 1010

PRESSURE

8
bar

FLOW RATE

600
l/h

ABSORBED POWER

0,8
kW

EXCLUSIVE TECNOLOGIES

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



MOST FREQUENTLY USE

AGRICULTURE



PUBLIC WORK



MUNICIPALITIES



INNOVATIONS



MSC™
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



MODULAR
BUILD-UP



IPC'S
EXCLUSIVE
BOILER

SPECS



STANDARD LIFTING HOOK TO
BE RAISED AND TRANSPORTED
ANYWHERE



DIRECT WATER SUPPLY OR
SUCTION WITH EXTERNAL
TANK



CONTROL PANEL SHOWING:
ON/OFF SWITCH, NETWORK
INDICATOR LIGHT, FLAME
CONTROL LIGHT, WARNING
LACK OF ANTISCALE, SERVICE
WARNING LIGHT (150 HRS),
READY WARNING LIGHT
(TEMPERATURE REACHED)

TECHNICAL DATA

GREEN JET 1010 M		
Code	GNVA40051	
Operating pressure	bar/Mpa	8/0,8
Flow rate	l/h	600
Outlet water temperature max	°C	~100
Power supply	Ph-V-Hz/A	1-230-50/3,8
Absorbed power	kW	0,8
Motor power	kW	0,55
Remote control	DTS	
Pump(type)	IPC volumetric rotary vane pump is self-priming, high-performance. The pump body is brass made	
Boiler thermal power	kW	74
Fuel consumption	Kg/h	5,2
Fuel tank	l	18
Antiscale tank	l	2
Dimension (LxWxH)	cm	83x109x100
Weight	Kg	142

STANDARD EQUIPMENT

CODE: IPPR40027
HANDGRIP ML330 +
EXTENSION 350 mm



CODE: LCLC40025
70 cm LANCE WITH SPRAY
BAR (SPRAY BAR L= 50 cm)



CODE: TBAP39122
H.P. HOSE 20 m
(NO-MARKING)



OPTIONAL

CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg





HOT WATER WEED REMOVAL SYSTEM



GREEN JET 7510

PRESSURE

75
bar

FLOW RATE

600
l/h

ABSORBED POWER

1,9
kW

EXCLUSIVE TECNOLOGIES

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



SPECIAL APPLICATIONS - CLEANING, WASHING AND WEED CONTROL WITH ONE MACHINE

MOST FREQUENTLY USE

AGRICULTURE

PUBLIC WORK

MUNICIPALITIES

INNOVATIONS



MSCMTM
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



MODULAR
BUILD-UP



IPC'S
EXCLUSIVE
BOILER

SPECS



2 FIXED PNEUMATIC WHEELS AND 2 PIVOT WHEELS (1 WITH BREAK)



DIRECT WATER SUPPLY OR SUCTION WITH EXTERNAL TANK



CONTROL PANEL SHOWING: BURNER LOCKOUT INDICATOR LIGHT, WARNING LACK OF ANTISCALE, SCHEDULED MAINTENANCE (150 HRS), MAX TEMPERATURE INDICATOR (TEMPERATURE REACHED).

TECHNICAL DATA

GREEN JET 7510 M		
GNVA40078		
Code		
Operating pressure	bar/Mpa	75/7,5
Flow rate	l/h	600
Outlet water temperature max	°C	~100 (constant temperature)
Power supply	Ph-V-Hz/A	1-230-50
Absorbed power	kW	1,9
Motor power	kW	4-1400
Remote control		DTS
Pump(type)		IPC plunger/brass/ceramic
Boiler thermal power	kW	75
Fuel consumption	Kg/h	6,3
Fuel tank	l	18
Antiscale tank	l	2
Dimension (LxWxH)	cm	83x109x100
Weight	Kg	142

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR89117
70 cm DOUBLE STAINLESS
STEEL LANCE



CODE: TBAP40229
H.P. HOSE 10 m 1/4"



CODE: LCLC40025
70 cm LANCE WITH SPRAY
BAR (SPRAY BAR L= 50 cm)



OPTIONAL

CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg





HIGH-PRESSURE WASHERS - HOT WATER

PW-H10

PRESSURE

120÷140
bar

FLOW RATE

430÷450
l/h

ABSORBED POWER

2,1÷2,5
kW



PW-H10 P I 1408 AOM

EXCLUSIVE CHARACTERISTICS

- ▶ IMMEDIATE TOTAL STOP - ITS
- ▶ BOILER IGNITION DELAY - IBD

MOST FREQUENTLY USE

DIY AND GARDENING



INNOVATIONS



G6000™
CERAMIC
TECH GUN

SPECS



LARGE FRONT FOOT FOR
GREATER STABILITY



STURDY ERGONOMIC
HANDLE FOR AN EASY
MANOEUVRABILITY



4 LITRES DIESEL TANK MADE
OF TRANSPARENT PLASTIC, IN
ORDER TO ENSURE CONSTANT
MONITORING OF DIESEL LEVEL

TECHNICAL DATA

		WITHOUT HOSE REEL		WITH HOSE REEL
		PW-H10 I1207AA M	PW-H10 I1408AA M	PW-H10P I1408AO M
Code		IDAC40572	IDAC40573	IDAC40574
PERFORMANCE				
Operating pressure	bar/Mpa	120/12	140/14	140/14
Flow rate	l/h	430	450	450
Outlet water temperature	°C	60	60	60
Power supply	Ph-V-Hz/A	1-230-50/9,4	1-230-50/9,7	1-230-50/11,2
Absorbed power	kW	2,1	2,3	2,5
Motor pole/rpm		2-2800	2-2800	2-2800
Remote control		ITS	ITS	ITS
Pump/head/pistons		Axial/aluminium/inox	Axial/aluminium/inox	Axial/brass/inox
Boiler thermal power	kW	26	26	26
Fuel consumption	kg/h	1,8	1,9	1,9
Fuel tank	l	4	4	4
Detergent tank	l	-	-	-
Detergent delivery		low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	68x48x75	68x48x75	68x48x75
Weight	kg	44	50	55

STANDARD EQUIPMENT

CODE: IPPR40017
HANDGRIP MV2009
(FOR I1207AA/I1408AA)



CODE: IPPR40025
HANDGRIP G6000
(FOR I1408AO)



CODE: LCPR40037
EXTENSION P50
ZINC PLATED (FOR
I207AA/I408AA)



CODE: LCPR40071
LANCE WITH MULTIREG
NOZZLE Ø 1,10
(FOR I408AO)



CODE: UGLN49985
H.P NOZZLE 1/4 1503
(FOR I207)



CODE: UGLN75421
H.P NOZZLE 1/4 15025
(FOR I408AO)



CODE: TBAP28305
HIGH PRESSURE HOSE 8 m
(FOR I1207AA/I1408AA)



CODE: TBAP93872
HIGH PRESSURE HOSE 8 m
(FOR I1408AO)



CODE: LCPR40038
FOAMER M22
(FOR I1207AA/I1408AA)



CODE: LCPR40040
FOAMER M22 I I
(FOR I1408AO)



CODE: LCPR40011
TURBO LANCE M22 D. 1,15
(FOR I408AO)



OPTIONAL ACCESSORIES

CODE: SPID24911
ROTATING HYDROBRUSH
LANCE



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCPR14857
SANDBLASTER KIT Ø 1,2 mm
(FOR I408)



CODE: PRCH40041
SAND BAG 25 Kg





HIGH-PRESSURE WASHERS - HOT WATER

PW-H28

PRESSURE

130÷170
bar

FLOW RATE

500÷800
l/h

ABSORBED POWER

2,5÷4,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ IMMEDIATE TOTAL STOP - ITS ("I" MODELS)
- ▶ IGNITION BOILER DELAY - IBD
- ▶ IPC TEMPERATURE STABILIZER - ATC
- ▶ DELAYED TOTAL STOP - DTS ("D" MODELS)
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ IGNITION BOILER DELAY - IBD
- ▶ IPC TEMPERATURE STABILIZER - ATC



PW-H28/4

PW-H28

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSC™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER

SPECS



LARGE DIAMETER WHEELS
IN ORDER TO FACILITATE
MOVEMENTS



ACCESSORY STORAGE
COMPARTMENT



STURDY AND LARGE TANK
IN ROTOMOULDED PLASTIC
MATERIAL

TECHNICAL DATA

		IMMEDIATE TOTAL STOP VERSION		DELAYED TOTAL STOP VERSION	
3 WHEELS		PW-H28 I1308A M		PW-H28 D1309P M	PW-H28 D1713P T
Code		IDAC40680		IDAC40681	IDAC40682
4 WHEELS		PW-H28/4 I1308A M		PW-H28/4 D1309P M	PW-H28/4 D1713P T
Code		IDAC40683		IDAC40684	IDAC40685
PERFORMANCE					
Operating pressure	bar/Mpa	40-130/4-13		40-130/4-13	40-170/4-17
Flow rate	l/h	240-500		280-540	400-800
Outlet water temperature	°C	30-110		30-130	30-130
Power supply	Ph-V-Hz/A	1-230-50/12,3		1-230-50/11,5	3-400-50/9,1
Absorbed power	kW	2,7		2,5	4,7
Motor pole/rpm		2-2800		2-2800	2-2800
Remote control		ITS		DTS	DTS
Pump/head/pistons		Axial/brass/ceramic		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	37,8		37,8	37,8
Fuel consumption	kg/h	3,2		3,2	3,2
Fuel tank	l	18		18	18
Detergent tank	l	-		-	-
Detergent delivery		low pressure		low pressure	low pressure
Dimension (LxWxH)	cm	82x63x87		82x63x87	82x63x87
Weight	kg	75		80	90

STANDARD EQUIPMENT

CODE: IPPR40017
HANDGRIP MV2009
(FOR 1308)



CODE: IPPR40025
HANDGRIP G6000
(FOR 1309/1713)



CODE: LCPR40037
EXTENSION P50 ZINC
PLATED



CODE: UGLN11196
H.P. NOZZLE 1/4 15035
(FOR 1308)



CODE: UGLN40000
H.P. NOZZLE 1/4 15034
(FOR 1309)



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 1713)



CODE: TBAP28305
HIGH PRESSURE HOSE 8 m



OPTIONAL ACCESSORIES

CODE: LCPR29362
HYDROBRUSH LANCE



CODE: SPID24939
FIXED HYDROBRUSH LANCE



CODE: KTRI40303
HOSE REEL KIT



CODE: LCPR40040
FOAMER KIT 1 l



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT 10 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40103
EXTENSION P70 + TPR255
Ø 0,4 - (FOR 1713)



CODE: LCPR40104
EXTENSION P70 + TPR255
Ø 0,35 (FOR 1308/1309)



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3 mm
(FOR 1308/1309)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 1713)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCLC49492
LANCE FOR WASHING
FLOORS Ø 0,35



CODE: KTRI40306
MAINTENANCE KIT 500H
(FOR 1309)



CODE: KTRI40307
MAINTENANCE KIT 500H
(FOR 1713)





HIGH-PRESSURE WASHERS - HOT WATER

PW-H28/4

STAINLESS STEEL COVER

PRESSURE

130 ÷ 170
bar

FLOW RATE

600 ÷ 800
l/h

ABSORBED POWER

2,7 ÷ 4,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ BOILER IGNITION DELAY - IBD
- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ IPC TEMPERATURE STABILIZER - ATC



WITH NO-MARKING RUBBER WHEELS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSC™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND
EASE TRANSPORT



STAINLESS STEEL COVER



LANCE HOLDER WITH
LOCKING SYSTEM

TECHNICAL DATA

		PW-H28/4 D1310P4 M	PW-H28/4 D1713P T
Code		IDAC41124	IDAC41125
PERFORMANCE			
Operating pressure	bar/Mpa	40-130/4-13	40-170/4-17
Flow rate	l/h	280-600	400-800
Outlet water temperature	°C	30-130	30-130
Power supply	Ph-V-Hz/A	1-230-50/12,3	3-400-50/9,1
Absorbed power	kW	2,7	4,7
Motor pole/rpm		4-1400	2-2800
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	37,8	37,8
Fuel consumption	kg/h	3,2	3,2
Fuel tank	l	18	18
Detergent tank	l	-	-
Detergent delivery		low pressure	low pressure
Dimension (LxWxH)	cm	82x63x87	82x63x87
Weight	kg	87	90

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP28305
H.P. HOSE 8 m



CODE: UGLN49986
H.P. NOZZLE 1/4 1504



OPTIONAL ACCESSORIES

CODE: LCPR29362
HYDROBRUSH LANCE



CODE: SPID24939
FIXED HYDROBRUSH LANCE



CODE: KTRI40303
HOSE REEL KIT



CODE: LCPR40040
FOAMER KIT 1 l



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT 10 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40103
EXTENSION P70 + TPR255 Ø0,4



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4



CODE: PRCH40041
SAND BAG 25 kg



CODE: LCLC49492
LANCE FOR WASHING FLOORS Ø 0,35



CODE: LCLC41140
LANCE FOR WASHING FLOORS INOX



CODE: TBAP39120
NO-MARKING HIGH PRESSURE HOSE 10 m



CODE: TBAP39122
NO-MARKING HIGH PRESSURE HOSE 20 m



CODE: KTRI40316
MAINTENANCE KIT 500H - (FOR 1310)



CODE: KTRI40307
MAINTENANCE KIT 500H - (FOR 1713)





HIGH-PRESSURE WASHERS - HOT WATER

PW-H50*

DELAYED TOTAL STOP MODELS

PRESSURE

100÷200
bar

FLOW RATE

600÷1000
l/h

ABSORBED POWER

3÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ BOILER IGNITION DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ IPC TEMPERATURE STABILIZER - ATC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU



PW-H50



PW-H50/4

* BASIC VERSION

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSCT™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE

SPECS



PUMP WITH BRASS HEAD,
CERAMIC PISTONS AND
VISIBLE OIL LEVEL



SEPARATED PRESSURE
REGULATING UNLOADER VALVE



2 LANCE HOLDERS, ONE WITH
LOCKING SYSTEM

TECHNICAL DATA

3 WHEELS

		PW-H50 D1310P4 M	PW-H50 D1012P4 M	PW-H50 D1813P4 T	PW-H50 D1915P4 T	PW-H50 D2017P4 T
Code		IDAC40868	IDAC40869	IDAC40870	IDAC40871	IDAC40872
		PW-H50/4 D1310P4 M	PW-H50/4 D1012P4 M	PW-H50/4 D1813P4 T	PW-H50/4 D1915P4 T	PW-H50/4 D2017P4 T
Code		IDAC40878	IDAC40879	IDAC40880	IDAC40881	IDAC40882

PERFORMANCE

Operating pressure	bar/Mpa	30-130/3-13	30-100/3-10	30-180/3-18	30-190/3-19	30-200/3-20
Flow rate	l/h	300-600	360-720	450-800	450-900	500-1000
Outlet water temperature	°C	30-140	30-140	30-140	30-140	30-140
Power supply	Ph-V-Hz/A	1-230-50/13,8	1-230-50/14	3-400-50/9,7	3-400-50/10,6	3-400-50/13,2
Absorbed power	kW	3,1	3,2	5	5	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	40	55	70	70	≥70
Fuel consumption	kg/h	3,2	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	110	110	120	122	140

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 1310/1813)



CODE: UGLN05200
H.P. NOZZLE 1/4 1505
(FOR 1012)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915/2017)



CODE: TBAP25324
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCLC49492
LANCE FOR WASHING FLOORS
Ø0,35 (FOR 1310/1915)



CODE: LCLC49494
LANCE FOR WASHING
FLOORS Ø0,55 (FOR 1012)



CODE: LCLC49493
LANCE FOR WASHING FLOORS
Ø0,45 (FOR 1813/2017)



CODE: KTRI40235
HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLING M22



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCPR40104
EXTENSIO P70 + TPR255
Ø0,35 (FOR 1310/1813)



CODE: LCPR40135
EXTENSIO P70 + TPR255
Ø0,45 (FOR 1012/1915/2017)



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 mm
(FOR 1915/2017)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 1310/1813)



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 mm
(FOR 1012)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X 6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40316
MAINTENANCE KIT 500H
(FOR 1310)



CODE: KTRI40314
MAINTENANCE KIT 500H
(FOR 1813/1915)



CODE: KTRI40430
MAINTENANCE KIT 500H
(FOR 1012)



CODE: KTRI40431
MAINTENANCE KIT 500H
(FOR 2017)





HIGH-PRESSURE WASHERS - HOT WATER

PW-H50 PLUS*

DELAYED TOTAL STOP MODELS

PRESSURE

100÷200
bar

FLOW RATE

600÷1000
l/h

ABSORBED POWER

3÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ BOILER IGNITION DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ ELECTRONIC TEMPERATURE STABILIZER CONTROL - ETSC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ MAINTENANCE CHECK LED - MCL



PW-H50 PLUS



PW-H50/4 PLUS

* PLUS VERSION

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSC™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE



ETC™
ELECTRONIC
TEMPERATURE
CONTROL

SPECS



CONTROL PANEL WITH
INDICATORS LAMPS



ERGONOMIC HANDLE PROVIDED
WITH LANCE HOLDER FOR AN
EASY TRANSPORT



ACCESSORIES STORAGE
COMPARTMENT

TECHNICAL DATA

3 WHEELS

		PW-H50P D1310P4 M	PW-H50P D1012P4 M	PW-H50P D1813P4 T	PW-H50P D1915P4 T	PW-H50P D2017P4 T
--	--	-------------------	-------------------	-------------------	-------------------	-------------------

Code		IDAC40873	IDAC40874	IDAC40875	IDAC40876	IDAC40877
------	--	-----------	-----------	-----------	-----------	-----------

4 WHEELS

		PW-H50P/4 D1310P4 M	PW-H50P/4 D1012P4 M	PW-H50P/4 D1813P4 T	PW-H50P/4 D1915P4 T	PW-H50P/4 D2017P4 T
--	--	---------------------	---------------------	---------------------	---------------------	---------------------

Code		IDAC40883	IDAC40884	IDAC40885	IDAC40886	IDAC40887
------	--	-----------	-----------	-----------	-----------	-----------

PERFORMANCE

Operating pressure	bar/Mpa	30-130/3-13	30-100/3-10	30-180/3-18	30-190/3-19	30-200/3-20
Flow rate	l/h	300-600	360-720	450-800	450-900	500-1000
Outlet water temperature	°C	30-140	30-140	30-140	30-140	3-140
Power supply	Ph-V-Hz/A	1-230-50/13,8	1-230-50/14	3-400-50/9,7	3-400-50/10,6	3-400-50/13,2
Absorbed power	kW	3,1	3,2	5	5	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	40	55	70	70	≥70
Fuel consumption	kg/h	3,2	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	107	109	120	122	140

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 1310/1813)



CODE: UGLN05200
H.P. NOZZLE 1/4 1505
(FOR 1012)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915/2017)



CODE: TBAP25324
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCLC49492
LANCE FOR WASHING FLOORS
Ø 0,35 (FOR 1310/1915)



CODE: LCLC49494
LANCE FOR WASHING
FLOORS Ø 0,55 (FOR 1012)



CODE: LCLC49493
LANCE FOR WASHING FLOORS
Ø 0,45 (FOR 1813/2017)



CODE: KTRI40235
HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLING M22



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCPR40104
EXTENSIO P70 + TPR255
Ø 0,35 (FOR 1310/1813)



CODE: LCPR40135
EXTENSIO P70 + TPR255
Ø 0,45
(FOR 1012/1915/2017)



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 mm
(FOR 1915/2017)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 1310/1813)



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 mm
(FOR 1012)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X 6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40316
MAINTENANCE KIT 500H
(FOR 1310)



CODE: KTRI40314
MAINTENANCE KIT 500H
(FOR 1813/1915)



CODE: KTRI40430
MAINTENANCE KIT 500H
(FOR 1012)



CODE: KTRI40431
MAINTENANCE KIT 500H
(FOR 2017)





HIGH-PRESSURE WASHERS - HOT WATER

PW-H90*

PRESSURE

150÷190
bar

FLOW RATE

1300
l/h

ABSORBED POWER

7,1÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC



* BASIC VERSION

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



IPC
PUMP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONNECTION BETWEEN PUMP AND MOTOR IS PROVIDED WITH FLEXIBLE COUPLING



ELECTRIC PANEL IS PROVIDED WITH A TRANSPARENT COVER IN ORDER TO PROTECT IT FROM SPLASHES AND DIRT



ERGONOMIC HANDLE FOR AN EASY TRANSPORT

TECHNICAL DATA

		WITHOUT HOSE REEL	
		PW-H90 D1521P T	PW-H90 D1921P T
Code		IDAC40361	IDAC40362
PERFORMANCE			
Operating pressure	bar/Mpa	40-150/4-15	40-190/4-19
Flow rate	l/h	650-1300	650-1300
Outlet water temperature	°C	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/13	3-400-50/16
Absorbed power	kW	7,1	8,5
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Boiler thermal power	kW	85,5	85,5
Fuel consumption	kg/h	7,6	7,6
Fuel tank	l	30	30
Detergent tank	l	16	16
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	131x77x95	131x77x95
Weight	kg	175	182

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40160
EXTENSION PD70 INOX 0°



CODE: UGLN49997
H.P. NOZZLE 1/4 25075
(FOR 1521 - 2PCS)



CODE: UGLN49996
H.P. NOZZLE 1/4 2507
(FOR 1921- 2PCS)



CODE: TBAP40009
HIGH PRESSURE HOSE
10 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: LCPR29363
STEAM LANCE - P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS



CODE: RCIN10810
HOSE COUPLING M22



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 1921)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR40088
EXTENSION P70 -
TURBO 0.80



CODE: TBAP24406
DRAIN KIT 20 m



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X 6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40433
MAINTENANCE KIT 500H





HIGH-PRESSURE WASHERS - HOT WATER

PW-H100*

PRESSURE

170÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

7,5÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ BOILER IGNITION DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ IPC TEMPERATURE STABILIZER - ATC



PW-H100/4

PW-H100

* BASIC VERSION

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSC™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE

SPECS



STURDY AND LARGE TANKS
IN ROTOMOULDED PLASTIC
MATERIAL



BOILER CAN BE OPENED
FROM THE TOP FOR AN EASY
CLEANING



2 LANCE HOLDERS, ONE WITH
LOCKING SYSTEM

TECHNICAL DATA

3 WHEELS

Code

PW-H100 D2515P T

IDAC40888

PW-H100 D1721P T

IDAC40889

PW-H100 D2021P T

IDAC40890

4 WHEELS

Code

PW-H100/4 D2515P T

IDAC40894

PW-H100/4 D1721P T

IDAC40895

PW-H100/4 D2021P T

IDAC40896

PERFORMANCE

Operating pressure	bar/Mpa	30-250/3-25	30-170/3-17	30-200/3-20
Flow rate	l/h	450-900	650-1300	650-1300
Outlet water temperature	°C	30-140	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/16	3-400-50/14,6	3-400-50/16,6
Absorbed power	kW	7,7	7,9	8,5
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	≥70	≤100	≤100
Fuel consumption	kg/h	5,8	7,4	7,4
Fuel tank	l	25	25	25
Detergent tank	l	22	22	22
Detergent delivery		high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90
Weight	kg	172	142	172

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN49997
H.P. NOZZLE 1/4 25075
(FOR 1721)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: TBAP40009
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 2021)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 2515)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: TBAP24406
DRAIN KIT 20 m
(for 1721/2021)



CODE: LCPR40103
EXTENSION P70 + TPR255
Ø0,4 (FOR 2515)



CODE: LCPR40171
EXTENSION P70 + R.J.255
Ø0,65 (FOR 2021)



CODE: LCPR40170
EXTENSION P70 + R.J.255
Ø0,75 (FOR 1721)



CODE: LCPR29363
STEAM LANCE - P70



CODE: KTRI40341
HOOSE REEL KIT



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40434
MAINTENANCE KIT 500H
(FOR 1721/2021)



CODE: KTRI40435
MAINTENANCE KIT 500H
(FOR 2515)





HIGH-PRESSURE WASHERS - HOT WATER

PW-H100 P

PRESSURE

170÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

7,5÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ BOILER IGNITION DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ELECTRONIC TEMPERATURE STABILIZER CONTROL - ETSC
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



PW-H100 PLUS

PW-H100/4 PLUS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSC™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE



ETC™
ELECTRONIC
TEMPERATURE
CONTROL

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS



PRESSURE REGULATING
UNLOADER VALVE BOLT ON
TYPE



EASILY ACCESSIBLE
ANTISCALE TANK

TECHNICAL DATA

3 wheels		PW-H100P D2515P T	PW-H100P D1721P T	PW-H100P D2021P T
Code		IDAC40891	IDAC40892	IDAC40893
4 wheels		PW-H100/4P D2515P T	PW-H100/4P D1721P T	PW-H100/4P D2021P T
Code		IDAC40897	IDAC40898	IDAC40899
PERFORMANCE				
Operating pressure	bar/Mpa	30-250/3-25	30-170/3-17	30-200/3-20
Flow rate	l/h	450-900	650-1300	650-1300
Outlet water temperature	°C	30-140	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/16	3-400-50/14,6	3-400-50/16,6
Absorbed power	kW	7,7	7,9	8,5
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Boiler thermal power	kW	≥70	≤100	≤100
Fuel consumption	kg/h	5,8	7,4	7,4
Fuel tank	l	25	25	25
Detergent tank	l	22	22	22
Detergent delivery		high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90
Weight	kg	172	142	172

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN49997
H.P. NOZZLE 1/4 25075
(FOR 1721)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: TBAP40009
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70




CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70




CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 2021)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 2515)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: TBAP24406
DRAIN KIT 20 m
(for 1721/2021)



CODE: LCPR40103
EXTENSION P70 + TPR255
Ø0,4 (FOR 2515)



CODE: LCPR40171
EXTENSION P70 + R.J.255
Ø0,65 (FOR 2021)



CODE: LCPR40170
EXTENSION P70 + R.J.255
Ø0,75 (FOR 1721)



CODE: LCPR29363
STEAM LANCE - P70



CODE: KTRI40341
HOSE REEL KIT



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40434
MAINTENANCE KIT 500H
(FOR 1721/2021)



CODE: KTRI40435
MAINTENANCE KIT 500H
(FOR 2515)





HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

PW-E100

ELECTRICALLY HEATED BOILER

PRESSURE

170
bar

FLOW RATE

600÷720
l/h

ABSORBED POWER

16,3÷35,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

- WITHOUT EXHAUST GAS
- GREATER EFFICIENCY WITHOUT USE FUEL



WITH NO-MARKING RUBBER WHEELS

MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSCT™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN

SPECS



LARGE WHEELS IMPROVE MANEUVERABILITY AND EASE TRANSPORT.



22L DETERGENT TANK AND 25L ANTISCALE TANK.



3 STAGE HIGH EFFICIENCY BOILER WITH AISI 316 STAINLESS STEEL STRUCTURE.

TECHNICAL DATA

Code		PW-E100 D1710 P12 T IDAC41121	PW-E100 D1712 P24 T IDAC41122	PW-E100 D1712 P36 T IDAC41123
PERFORMANCE				
Operating pressure	bar/Mpa	30-170/3-17	30-170/3-17	30-170/3-17
Flow rate	l/h	450-600	450-720	450-720
Outlet water temperature	°C	70	70	70
Power supply	Ph-V-Hz/A	3-400-50/25	3-400-50/43,2	3-400-50/53
Absorbed power	kW	16,3	29	35,7
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	24	36
Antiscale tank	l	25	25	25
Detergent tank	l	22	22	22
Detergent delivery		high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90
Weight	Kg	113	113	113

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN49986
H.P. NOZZLE 1/4" 1504 -
(FOR 24kW/ 36kW)



CODE: UGLN11196
H.P. NOZZLE 1/4" 15035 -
(FOR 12kW)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI40542
REMOTE CONTROL





HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

PW-E100

ELECTRICALLY HEATED BOILER

PRESSURE

140 bar

FLOW RATE

240 l/h

ABSORBED POWER

16,3÷29
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

- WITHOUT EXHAUST GAS
- GREATER EFFICIENCY WITHOUT USE FUEL



SPECIAL - LOW WATER FLOW

WITH NO-MARKING RUBBER WHEELS

MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSCT™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN

SPECS



LARGE WHEELS IMPROVE MANEUVERABILITY AND EASE TRANSPORT.



22L DETERGENT TANK AND 25L ANTISCALE TANK.



3 STAGE HIGH EFFICIENCY BOILER WITH AISI 316 STAINLESS STEEL STRUCTURE.

TECHNICAL DATA

		PW-E100 D1404 P12 T	PW-E100 D1404 P24 T
Code		IDAC41288	IDAC41289
PERFORMANCE			
Operating pressure	bar/Mpa	30-140/3-14	30-140/3-14
Flow rate	l/h	240	240
Outlet water temperature max.	°C	80	80
Power supply	Ph-V-Hz	3-400-50	3-400-50
Absorbed power	kW	16,3	29
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	24
Antiscale tank	l	25	25
Detergent tank	l	22	22
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	Cm	110x70x90	110x70x90
Weight	Kg	113	113

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN22109
H.P. NOZZLE 1/4" 1515



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI40542
REMOTE CONTROL





HIGH-PRESSURE WASHERS - HOT WATER

PW-H100 P

STAINLESS STEEL COVER

PRESSURE

170÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

5÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ELECTRONIC TEMPERATURE STABILIZER CONTROL - ETSC
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



STAINLESS STEEL COVER

WITH NO-MARKING RUBBER WHEELS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSC™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND EASE
TRANSPORT



STAINLESS STEEL COVER



HANDLE AND TANKS IN
ROTOMOULDED PLASTIC MATERIAL

TECHNICAL DATA

		PW-H100P D1915P T	PW-H100P D2017P T	PW-H100P D1721P T	PW-H100P D2021P T	PW-H100P D2515P T
Code		IDAC41126	IDAC41127	IDAC41128	IDAC41129	IDAC41130
PERFORMANCE						
Operating pressure	bar/Mpa	30-190/3-19	30-200/3-20	30-170/3-17	30-200/3-20	30-250/3-25
Flow rate	l/h	450-900	500-1000	650-1300	650-1300	450-900
Outlet water temperature	°C	30-140	30-140	30-140	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/10,6	3-400-50/13,2	3-400-50/14,6	3-400-50/16,6	3-400-50/16
Absorbed power	kW	5	6,4	7,9	8,5	7,7
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	70	≥70	≤100	≤100	≥70
Fuel consumption	Kg/h	5,8	5,8	7,4	7,4	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	Kg	144,70	168,60	158	186,60	186,60

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°
(FOR 1721/2021/2515)



CODE: LCPR40087
EXTENSION P70
INOX(FOR 1915/2017)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915/2017)



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN49997
H.P. NOZZLE 1/4 25075
(FOR 1721)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: TBAP40009
H.P. HOSE 10 m R2 5/16"
(FOR 1721/2021/2515)



CODE: TBAP25324
H.P. HOSE 10 m R1 5/16"
(FOR 1915/2017)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: SPID24939
FIXED HYDRO BRUSH
LANCE



CODE: LCLC41140
LANCE FOR WASHING
FLOORS



CODE: LCPR29363
STEAM LANCE P70



CODE: LCPR14858
SANDBLASTER KIT D. 1,4
(FOR 2515)



CODE: LCPR14859
SANDBLASTER KIT D. 1,5
(FOR 1915/2017)



CODE: LCPR14860
SANDBLASTER KIT D. 1,7
(FOR 2021)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP23853
DRAIN KIT 10 m
(FOR 1915/2017)



CODE: TBAP24406
DRAIN KIT 20 m
(FOR 1721/2021)



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: TBAP39120
NON-MARKING H.P.
HOSE R1 10 m 5/16"
(1915/2017/1721)



CODE: TBAP39121
NON-MARKING H.P. HOSE
R2 10 m 5/16"
(FOR 2021P4/2515P4)



CODE: TBAP39122
NON-MARKING H.P.
HOSE R1 20 m 5/16"
(1915/2017/1721)



CODE: TBAP39123
NON-MARKING H.P. HOSE
R2 20 m 5/16"
(FOR 2021P4/2515P4)



CODE: LCPR40135
EXTENSION P70 + TPR255
Ø0,45 - (FOR 1915/2017)



CODE: LCPR40103
EXTENSION P70 + TPR255
Ø0,4 - (FOR 2515)



CODE: LCPR40171
EXTENSION P70 + R.J.255
Ø0,65 - (FOR 2021)



CODE: LCPR40170
EXTENSION P70 + R.J.255
Ø0,75 - (FOR 1721)



CODE: KTRI40314
MAINTENANCE KIT 500H
(FOR 1915)



CODE: KTRI40431
MAINTENANCE KIT 500H
(FOR 2017)



CODE: KTRI40434
MAINTENANCE KIT 500H
(FOR 1721/2021)



CODE: KTRI40435
MAINTENANCE KIT 500H
(FOR 2515)





HIGH PRESSURE WASHERS - HOT WATER



PW-H100 HTM

PRESSURE

200 bar

FLOW RATE

900 l/h

ABSORBED POWER

6,4 kw

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ IGNITION BOILER DELAY - IBD
- ▶ ELECTRONIC TEMPERATURE STABILIZER - ETSC
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ MAINTENANCE CHECK LED - MCL
- ▶ INFRARED FLAME TEMPERATURE CONTRLOLS - FCS
- ▶ HIGH BRIGHTNESS LED SIGNALS - HBLS

MOST FREQUENTLY USE

AGRICULTURE/FARMING



AUTOMOTIVE



CONSTRUCTION



RETAIL



LOGISTICS AND TRANSPORT



INDUSTRY



COMMUNITIES



WASTE MANEGEMENT



ONE STEP
AHEAD



SPECIAL MACHINE: 100°C MAX TEMPERATURE, BOTH HIGH AND LOW PRESSURE MODE

(WITH NO-MARKING RUBBER WHEELS / 3 WHEELS)

INNOVATIONS



G6000™
CERAMIC
TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



IPC
PUMP



MODULAR
BUILD-UP



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE

SPECS



WARNING LAMP INFORMS
WHEN TEMPERATURE IS
BETWEEN 90-100°C



PRESSURE REGULATING
UNLOADER VALVE BOLT-ON
TYPE



COMPLETE WITH NON
MARKING WHEELS FOR FLAT
SURFACED

TECHNICAL DATA

3 WHEELS

PW-H100HT D2015P T

IDAC41248

Code

PERFORMANCE

Operating pressure	bar/Mpa	30-200/3-20
Flow rate	l/h	450-900
Outlet water temperature	°C	100
Power supply	Ph-V-Hz	3-400-50/13
Absorbed power	kW	6.4
Motor pole / rpm		4-1400
Remote control		DTS
Pump/head/pistons		lpc plunger/brass/ceramic
Boiler thermal power	kW	100
Fuel consumption	Kg/h	7.4
Fuel tank	l	25
Detergent tank	l	22
Detergent delivery		High pressure
Dimensions (LxWxH)	cm	110x70x90
Weight	Kg	140

STANDARD EQUIPMENT

CODE: IPPR40029
HANDGRIP G6000
WITH CERAMIC VALVE



CODE: LCPR40191
EXTENSION PD70 cm
INOX



CODE: UGLN05200
H.P. NOZZLE 1/4 1505



CODE: UGLN07790
L.P. NOZZLE 1/4 2513



CODE: TBAP40237
H.P. HOSE 10MT 1/4"
(NO-MARKING)



OPTIONAL ACCESSORIES

CODE: KTRI40341
HOSE REEL KIT



CODE: LCLC41140
LANCE FOR WSHING
FLOORS INOX



CODE: PRCH40039
ANTISCALE TREATMENT
M421 1KgX6



CODE: PRCH40040
ANTISCALE TREATMENT
M421 10Kg



CODE: KTRI40568
MAINTENANCE KIT 500H



CODE: RCIN10810
HOSE COUPLING M22



CODE: LCLC40027
STAINLESS STEEL FLOOR
CLEANER





HIGH-PRESSURE WASHERS - HOT WATER

TWOCK-H

PRESSURE

130÷200
bar

FLOW RATE

1800÷2500
l/h

ABSORBED POWER

11÷12,8
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



IPC'S
EXCLUSIVE
BOILER

SPECS



FLEXIBLE COUPLING
BETWEEN MOTOR AND PUMP



CONTROL PANEL PROVIDED
WITH EMERGENCY
SHUTDOWN



PLUNGER PUMP WITH SIX
CERAMIC PISTONS AND TWO
BRASS HEADS

TECHNICAL DATA

		TWOCK-H D1341PI T	TWOCK-H D2030PI T
Code		IDAC49714	IDAC49713
PERFORMANCE			
Operating pressure	bar/Mpa	30-130/3-13	30-200/3-20
Flow rate	l/h	2500	1800
Outlet water temperature	°C	30-150	30-150
Power supply	Ph-V-Hz/A	3-400-50/24,9	3-400-50/24
Absorbed power	kW	11	12,8
Motor pole/rpm		4-1400	6-1000
Remote control		DTS	DTS
Pump/head/pistons		IPC plunger/ 2 brass/ceramic	IPC plunger/ 2 brass/ceramic
Boiler thermal power	kW	81	81
Fuel consumption	kg/h	8,4 x 2	8,4 x 2
Fuel tank	l	54	54
Detergnt tank	l	-	-
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	140x86x86	140x86x86
Weight	kg	448	480

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN02317
H.P. NOZZLE 1/4 2515 (FOR 1341)



CODE: UGLN02312
H.P. NOZZLE 1/4 2509 (FOR 2030)



CODE: TBAP40011
HIGH PRESSURE HOSE 15 m



OPTIONAL ACCESSORIES

CODE: LCPR29363
STEAM LANCE - P70



CODE: PRCH40039
ANTI-SCALE TREATMENT M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT M421 10 Kg



CODE: LCPR40089
EXTENSION P70 TURBO D.1.0 (FOR 2030)



CODE: KTRI28935
LANCE HOLDER



CODE: KTRI28914
ROTATING ARM



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: AVTB39119
INOX HOSE REEL KIT





HIGH-PRESSURE WASHERS - HOT WATER

SKID FUEGO

PRESSURE

180 bar

FLOW RATE

1080 l/h

ENGINE POWER

11 Hp

EXCLUSIVE CHARACTERISTICS

- ▶ BY-PASS - BYP
- ▶ ENGINE THROTTLE CONTROL - RS
- ▶ BOILER IGNITION DELAY - IBD

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



PETROL ENGINE

INNOVATIONS



G6000™
CERAMIC
TECH GUN



M421
ANTI-SCALE



IPC'S
EXCLUSIVE
BOILER

SPECS



POWERFUL HONDA GX 340 LX
AIR COOLED 4 STROKE OHV
PETROL ENGINE



EPOXY POLYESTER POWDER
COATED TUBULAR FLAME-
TROLLEY



MOBILE UNITS OR TRUCK
MOUNTED

TECHNICAL DATA

		SKID FUEGO-H L1818PI P	
Code		IDAC49710	
PERFORMANCE			
Operating pressure	bar/Mpa	70-180/7-18	
Flow rate	l/h	680-1080	
Outlet water temperature	°C	80-120	
Engine type		Honda GX340 LX (gasoline)	
Engine power	Hp	11	
Engine speed	Rpm	1800	
Remote control		BY-PASS	
Pump/head/pistons		Plunger/brass/ceramic	
Boiler thermal power	kW	67	
Fuel consumption	kg/h	5,6	
Fuel tank	l	26	
Detergent tank	l	optional (16 l)	
Detergent delivery		high pressure	
Dimension (LxWxH)	cm	117x68x87	
Weight	kg	235,4	

STANDARD EQUIPMENT

CODE: IPPR40025 HANDGRIP G6000	CODE: LCPR40159 EXTENSION P70 INOX 0°	CODE: UGLN49994 H.P. NOZZLE 1/4 2506	CODE: TBAP40009 HIGH PRESSURE HOSE 10 m
			

OPTIONAL ACCESSORIES

CODE: LCPR29360 MUDGUARD LANCE - P90	CODE: LCPR24906 LANCE WITH DOUBLE NOZZLE HOLDER	CODE: LCPR29363 STEAM LANCE - P70	CODE: SPID24939 FIXED HYDROBRUSH LANCE	CODE: LCPR29362 HYDROBRUSH LANCE
				
CODE: RCIN10810 HOSE COUPLINGS	CODE: TBAP24406 DRAIN KIT 20 m	CODE: LCPR88522 EXTENSION P70 TURBO D. 0.65	CODE: KTRI37674 HOSE REEL KIT P 35-15 WALL	CODE: KTRI26685 TROLLEY KIT P 1-15 (WITH 3 WHEELS)
				PICTURE NOT AVAILABLE
CODE: KTRI27587 HOSE REEL KIT P35-7 (FOR KTRI26685)	CODE: KTRI26686 TROLLEY KIT P 1-16 (WITH 4 WHEELS)	CODE: KTRI26688 HOSE REEL KIT P35-5 (FOR KTRI26686)	CODE: KTRI26687 LANCE HOLDER KIT	CODE: KTRI26690 DETERGENT TANK
PICTURE NOT AVAILABLE	PICTURE NOT AVAILABLE	PICTURE NOT AVAILABLE	PICTURE NOT AVAILABLE	PICTURE NOT AVAILABLE
CODE: KTRI26689 DESCALING DEVICE	CODE: AVTB39119 STAINLESS STEEL HOSE REEL	CODE: KTRI28914 ROTATING ARM	CODE: LCPR14860 SANDBLASTER KIT D.1,7	CODE: PRCH40041 SAND BAG 25 Kg
PICTURE NOT AVAILABLE				
CODE: PRCH00039 ANTISCALE TREATMENT M421 (1 Kg X 6)	CODE: PRCH00040 ANTISCALE TREATMENT M421 10 Kg			
				



HIGH-PRESSURE WASHERS - HOT WATER STATIONARY

IWD-H

PRESSURE

100÷200
bar

FLOW RATE

720÷1260
l/h

ABSORBED POWER

3,2÷9,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ BOILER IGNITION DELAY - IBD
- ▶ FUEL LEVEL CONTROL - FLC (OPTIONAL)
- ▶ ANTI-SCALE LEVEL CONTROL - ALC (OPTIONAL)
- ▶ LIMESCALE/CORROSION PROTECT UNIT - LCPU
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



IPC'S
EXCLUSIVE
BOILER

SPECS



STAINLESS STEEL
STRUCTURE



PILOT LIGHTS INDICATING
MACHINE AND BURNER
FUNCTIONING, PLUS FLAME
CONTROL



PROFESSIONAL PRESSURE
GAUGE ENSURING A
CONSTANT CONTROL OF
WORKING PRESSURE

TECHNICAL DATA

		MUR. IWD-H D1012PI M IDAC48036	MUR. IWD-H D1615PI T IDAC48037	MUR. IWD-H D1618PI T IDAC48038	MUR. IWD-H D2015PI T IDAC48039	MUR. IWD-H D1521PI T IDAC48040	MUR. IWD-H D2021PI T IDAC48041
Code							
PERFORMANCE							
Operating pressure	bar/Mpa	100/10	160/16	165/16,5	200/20	150/15	200/20
Flow rate	l/h	720	900	1080	900	1260	1260
Outlet water max. temperature	°C	30-120	30-120	30-120	30-120	30-120	30-145
Power supply	Ph-V-Hz/A	1-230-50/14	3-400-50/10,5	3-400-50/13	3-400-50/14	3-400-50/13	3-400-50/16
Absorbed power	kW	3,2	6,5	7,2	7,2	7,2	9,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400	4-1400
Boiler thermal power	kW	67	67	88	88	88	88
Fuel consumption	l/h	5,8	5,8	7,4	7,4	7,4	7,4
Remote control		DTS	DTS	DTS	DTS	DTS	DTS
Fuel tank	l	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)
Detergent tank	l	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure	high pressure
Anti-scale tank	l	2	2	2	2	2	2
Pump/head/pistons		ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic
Dimension (LxWxH)	cm	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75
Weight	kg	170	185	190	186	186	210

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
**EXTENSION P70 INOX
(FOR 1012/1615/2015)**



CODE: LCPR40159
**EXTENSION P70 INOX 0°
(FOR 1618/1521/2021)**



CODE: UGLN49993
**H.P. NOZZLE 1/4 25055
(FOR 1012/1615)**



CODE: UGLN49995
**H.P. NOZZLE 1/4 25065
(FOR 1618/2021)**



CODE: UGLN49987
**H.P. NOZZLE 1/4 15045
(FOR 2015)**



CODE: UGLN49997
**H.P. NOZZLE 1/4 15075
(FOR 1521)**



CODE: TBAP40008
**H.P.HOSER 10 m 5/16"
(FOR 1012/1615/1618/1521)**



CODE: TBAP40009
**H.P.HOSER 2 10 m 5/16"
(FOR 2015)**



CODE: TBAP40010
**H.P.HOSER 2 10 m 3/8"
(FOR 2021)**



OPTIONAL ACCESSORIES

CODE: AVTB39119
INOX HOSE REEL KIT



CODE: KTRI28914
ROTATING ARM



CODE: LCLC41140
**LANCE FOR WASHING
FLOOR - INOX**



CODE: LCPR29360
MUDGUARD LANCE



CODE: KTRI48114
**REMOTE CONTROL WITH
DETERGENT + WAX CONTROL**



CODE: KTRI48110
WALL FIXING BRACKET



CODE: KTRI48111
STAND



CODE: LCPR41973
**TURBO LANCE Ø0,55 -
(FOR 1012/1615)**



CODE: LCPR88522
**TURBO LANCE Ø0,65 -
(FOR 1618/2021)**



CODE: LCPR40088
**TURBO LANCE Ø0,80 -
(FOR 2015/1521)**



CODE: LAFN48112
FLUE EXTENSION



CODE: LCPR13557
**SANDBLASTER KIT Ø 1,6 mm
(FOR 1012/1615)**



CODE: LCPR14860
**SANDBLASTER KIT Ø 1,7 mm
(FOR 1618/2021)**



CODE: LCPR14859
**SANDBLASTER KIT Ø 1,5 mm
(FOR 2015)**



CODE: PRCH40041
SAND BAG 25 Kg



CODE: MPVR13701
25 l FUEL TANK 1 PCS



CODE: MPVR13701
**25 l DETERGENT TANK
2 PCS**





HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

IWD-E

**ELECTRICALLY HEATED BOILER
STAINLESS STEEL SERIES**

PRESSURE

170
bar

FLOW RATE

600÷720
l/h

ABSORBED POWER

16,3÷35,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

- WITHOUT EXHAUST GAS
- GREATER EFFICIENCY WITHOUT USE FUEL



MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MSCT™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



PROFESSIONAL PRESSURE GAUGE ENSURING A COSTANT CONTROL OF WORKING PRESSURE.



HEAVY-DUTY STRUCTURE, WITH STAINLESS STEEL COVER.



3 STAGE HIGH EFFICIENCY BOILER WITH AISI 316 STAINLESS STEEL STRUCTURE.

TECHNICAL DATA

		IWD-E D1710 P12 T	IWD-E D1712 P24 T	IWD-E D1712 P36 T
Code		IDAC41134	IDAC41135	IDAC41136
PERFORMANCE				
Operating pressure	bar/Mpa	170/17	170/17	170/17
Flow rate	l/h	600	720	720
Outlet water temperature	°C	70	70	70
Power supply	Ph-V-Hz/A	3-400-50/25	3-400-50/43,2	3-400-50/53
Absorbed power	kW	16,3	29	35,7
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	24	36
Antiscale tank	l	6	6	6
Detergent tank	l	25 (optional)	25 (optional)	25 (optional)
Detergent delivery		high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	122x60x75	122x60x75	122x60x75
Weight	Kg	148,3	148,80	148,80

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN49986
H.P. NOZZLE 1/4" 1504 -
(FOR 24kW/ 36kW)



CODE: UGLN11196
H.P. NOZZLE 1/4" 15035 -
(FOR 12kW)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI48111
PAINTED STEEL STAND



CODE: KTRI40538
STAINLESS STEEL STAND



CODE: KTRI40536
REMOTE COTROL



CODE: MPVR13701
DETERGENT TANK 25 l



По вопросам продаж и поддержки обращайтесь:			
Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	